

AMENDMENTS TO THE CLAIMS

Please amend Claims 1-18 as shown below. This listing of claims will replace all prior versions, and listings, of claims in the international application.

1. *(currently amended)* A radio terminal equipment arrangement comprising:

a cellular core unit ~~(100)~~ comprising:

a control unit ~~(114)~~ for controlling the functions of the cellular core unit ~~(100)~~, the control unit ~~(114)~~ being configured to communicate with a cellular network ~~(120)~~ using a cellular connection, and to receive an incoming connection request from the cellular network ~~(120)~~; and

one or more peripheral units ~~(102, 104)~~ being configured to communicate with the cellular core unit ~~(100)~~ using a wireless low power radio frequency (LPRF) connection,

~~e-h-a-r-a-c-t-e-r-i-z-e-d~~ in that wherein:

the control unit ~~(114)~~ of the cellular core unit ~~(100)~~ is configured to indicate the incoming connection request in one or more peripheral units ~~(102, 104)~~ but not in the cellular core unit ~~(100)~~, when the LPRF connection between the cellular core unit ~~(100)~~ and a peripheral unit ~~(102, 104)~~ is available; and

the control unit ~~(114)~~ of the cellular core unit ~~(100)~~ is further configured to indicate the incoming connection request in the cellular core unit ~~(100)~~, when the LPRF connection between the cellular core unit ~~(100)~~ and the peripheral unit ~~(102, 104)~~ is not available, and to indicate the incoming connection request in the peripheral unit ~~(102, 104)~~, when the LPRF connection between the cellular core unit ~~(100)~~ and the peripheral unit ~~(102, 104)~~ becomes available.

2. *(currently amended)* The arrangement of claim 1, wherein ~~e-h-a-r-a-c-t-e-r-i-z-e-d~~ ~~in that~~ the control unit ~~(114)~~ of the cellular core unit ~~(100)~~ is configured to transfer the indication of the incoming connection request to the peripheral unit ~~(102, 104)~~, when during the indication of the incoming connection request in the cellular core unit ~~(100)~~ the LPRF connection between the cellular core unit ~~(100)~~ and the peripheral unit ~~(102, 104)~~ becomes available.

3. *(currently amended)* The arrangement of claim 1, wherein ~~characterized in that~~ the control unit (114) of the cellular core unit (100) is configured to check the incoming connection indication settings of the peripheral unit (102,104) with which the cellular core unit (100) has last been in LPRF connection and to indicate about the incoming connection request in the cellular core unit (100) according to the checked incoming connection indication settings of the peripheral unit (102,104).

4. *(currently amended)* The arrangement of claim 1, wherein ~~characterized in that~~ the control unit (114) of the cellular core unit (100) is configured to indicate about the incoming connection request on the cellular core unit (100) by signalling with a sound, a light or a vibration.

5. *(currently amended)* The arrangement of claim 1, wherein ~~characterized in that~~ the control unit (114) of the cellular core unit (100) is configured to indicate the incoming connection request on the cellular core unit (100), when during the indication concerning the incoming connection request to the peripheral unit (102,104) the LPRF connection between the cellular core unit (100) and the peripheral unit (102,104) is lost.

6. *(currently amended)* The arrangement of claim 1, wherein ~~characterized in that~~ the control unit (114) of the cellular core unit (100) is configured to:

establish an incoming connection to the peripheral unit (102) in which the incoming connection request has been accepted;

receive a connection request from another peripheral unit (104) than the peripheral unit (102) to which the incoming connection has been established;

indicate in the other peripheral unit (104) about transferring the connection to the other peripheral unit (104); and

transfer the established incoming connection from the peripheral unit (102) to which the incoming connection has already been established to the other peripheral unit (104) that has requested the connection.

7. *(currently amended)* The arrangement of claim 1, wherein ~~characterized in that~~ the arrangement further comprises a headset (103,105) connected to the peripheral unit (102,104) or to the cellular core unit (100) and the control unit (114)

is further configured to indicate in the peripheral unit (102, 104) if audios of the incoming connection are to be routed to the headset (103, 105).

8. *(currently amended)* The arrangement of claim 1, wherein ~~characterized in that~~ the arrangement further comprises a headset (105) connected to the cellular core unit (100), the peripheral unit (102, 104) is configured to accept the incoming connection and the control unit (114) is configured to indicate in the peripheral unit (102, 104) when the audios of the incoming connection are routed to the headset (105) connected to the cellular core unit (100).

9. *(currently amended)* The arrangement of claim 1, wherein ~~characterized in that~~ the LPRF connection between the cellular core unit (100) and the peripheral unit (102, 104) is a Bluetooth or a WLAN connection.

10. *(currently amended)* A method of indicating about an incoming connection in a radio terminal equipment arrangement comprising: a cellular core unit and one or more peripheral units, the cellular core unit communicating with one or more of the peripheral units using a wireless low power radio frequency (LPRF) connection, the method comprising:

receiving an incoming connection request from a cellular network by the cellular core unit[1, 2];

~~characterized by the method further comprising:~~

indicating (212) the incoming connection request in one or more of the peripheral units but not in the cellular core unit, when the LPRF connection between the cellular core unit and one or more of the peripheral units is available;

indicating (210) about the incoming connection request in the cellular core unit, when the LPRF connection between the cellular core unit and the peripheral unit is not available; and

indicating (212) about the incoming connection request in the peripheral unit, when the LPRF connection between the cellular core unit and the peripheral unit becomes available.

11. *(currently amended)* The method of claim 10, ~~characterized by the~~ method comprising transferring the indication of the incoming connection request to

the peripheral unit, when during the indication of the incoming connection request in the cellular core unit the LPRF connection between the cellular core unit and the peripheral unit becomes available.

12. *(currently amended)* The method of claim 10, the method comprising ~~e-h-a-r-a-c-t-e-r-i-z-e-d-b-y~~ checking (208) the incoming connection indication settings of a peripheral unit with which the cellular core unit has last been in connection with and indicating about the incoming connection request in the cellular core unit according to the checked incoming connection indication settings of the peripheral unit.

13. *(currently amended)* The method of claim 10, the method comprising ~~e-h-a-r-a-c-t-e-r-i-z-e-d-b-y~~ indicating about the incoming connection request in the cellular core unit by signalling with a sound, a light or a vibration.

14. *(currently amended)* The method of claim 10, the method comprising ~~e-h-a-r-a-c-t-e-r-i-z-e-d-b-y~~ indicating (210) about the incoming connection in the cellular core unit, when during the indication concerning the incoming connection request to the peripheral unit the LPRF connection between the cellular core unit and the peripheral unit is lost.

15. *(currently amended)* The method of claim 10, ~~e-h-a-r-a-c-t-e-r-i-z-e-d-b-y~~ the method further comprising:

establishing (314) an incoming connection to the peripheral unit in which the incoming connection request has been received;

receiving (316) a connection request from another peripheral unit;

indicating (318) in the other peripheral unit about transferring the connection to the other peripheral unit; and

transferring (320) the established incoming connection from the peripheral unit to the other peripheral unit.

16. *(currently amended)* The method of claim 10, ~~e-h-a-r-a-c-t-e-r-i-z-e-d-b-y~~ the method further comprising indicating (404) in the peripheral unit when audios of the

incoming connection are to be routed to a headset connected to the peripheral unit or to the cellular core unit.

17. *(currently amended)* The method of claim 10, ~~e-h-a-r-a-c-t-e-r-i-z-e-d~~ by the method further comprising accepting the incoming connection in the peripheral unit and indicating in the peripheral unit, when the audios of the incoming connection are routed to a headset connected to the cellular core unit.

18. *(currently amended)* The method of claim 10, ~~e-h-a-r-a-c-t-e-r-i-z-e-d~~ by wherein the LPRF connection between the cellular core unit and the peripheral unit ~~being~~ is a Bluetooth or a WLAN connection.